



ISO 9001:2000	DIMENSIONS							WT.	TENSILE STRENGTH
Part Number	Pitch	Roller Width	Roller Dia.	Pin Dia.	Link Plate Thk.	C	R	Per ft	Average
inch								lbs.	
2040	1	5/16	0.312	0.156	0.060	0.76	0.68	0.28	3700
2050	1 1/4	3/8	0.400	0.200	0.080	0.92	0.84	0.52	6100
2060	1 1/2	1/2	0.469	0.234	0.094	1.11	1.05	0.72	8500
2080	2	5/8	0.625	0.312	0.125	1.44	1.32	1.13	14500
C2040	1	5/16	0.312	0.156	0.060	0.76	0.68	0.34	3700
C2050	1 1/4	3/8	0.400	0.200	0.080	0.92	0.84	0.58	6100
C2060	1 1/2	1/2	0.469	0.234	0.125	1.18	1.18	1.05	8500
C2080	2	5/8	0.625	0.312	0.156	1.45	1.45	1.40	14500
25NP	1/4	1/8	0.130	0.090	0.030	0.37	0.34	0.09	875
35NP	3/8	3/16	0.200	0.141	0.050	0.56	0.50	0.22	2100
40NP	1/2	5/16	0.312	0.156	0.060	0.72	0.67	0.42	4000
50NP	5/8	3/8	0.400	0.200	0.080	0.89	0.83	0.68	6600
60NP	3/4	1/2	0.469	0.234	0.094	1.11	1.04	0.97	8500
80NP	1	5/8	0.625	0.312	0.125	1.44	1.32	1.70	14500
100NP	1 1/4	3/4	0.750	0.375	0.156	1.73	1.61	2.50	24000
120NP	1 1/2	1	0.875	0.437	0.187	2.14	2.00	3.70	34000
C2040NP	1	5/16	0.312	0.156	0.060	0.76	0.68	0.32	3700
C2050NP	1 1/4	3/8	0.400	0.200	0.080	0.92	0.84	0.55	6100
C2060HNP	1 1/2	1/2	0.469	0.234	0.125	1.25	1.18	0.97	8500

**FIT STRIVES FOR LONG-TERM, WIN-WIN BUSINESS RELATIONSHIPS**